

# SmartCompression™ EMT

## Submittal Sheet

SmartCompression EMT with pre-installed compression coupling saves time and money on every job. It allows for up to 3x faster installation compared to standard compression couplings, and its proprietary ID coating allows for faster wire-pulling. SmartCompression EMT is available in trade sizes 2-4 and 10' and 20' lengths.

### Listing

SmartCompression EMT is listed to safety standards UL-797 and UL-514B for fittings, and it is manufactured in accordance with ANSI® C80.3.



### Coatings

SmartCompression EMT is galvanized with a clear top coat, and the compression fitting is zinc-electroplated to inhibit corrosion.

### Locations

SmartCompression EMT is concrete tight. It is ideal for use wherever compression couplings are specified or preferred. Raintight available upon request.

## SmartCompression EMT Weights and Dimensions (10' Lengths)

Trade Size	Outside Diameter	Inside Diameter*	Wall Thickness	Minimum Weight EMT	Coupling Weight	Master Bundle Quantity	Master Bundle Weight
	in.	in.	in.	lbs./ft.	lbs.	ft.	lbs.
2	2.197	2.067	0.065	1.400	0.480	500	723
2½	2.875	2.731	0.072	2.050	1.060	350	757
3	3.500	3.356	0.072	2.500	1.300	300	832
3½	4.000	3.834	0.083	3.250	1.540	250	891
4	4.500	4.334	0.083	3.700	1.790	250	1010

\* For information only; not a standards requirement.

SmartCompression EMT is listed to safety standards UL-797 and UL-514B, and manufactured in accordance with ANSI® C80.3.

## Submittal Information

PROJECT: \_\_\_\_\_ CONTRACTOR: \_\_\_\_\_ DATE: \_\_\_\_\_

ENGINEER: \_\_\_\_\_ SPECIFICATION REFERENCE: \_\_\_\_\_ SYSTEM TYPE: \_\_\_\_\_

LOCATIONS: \_\_\_\_\_ COMMENTS: \_\_\_\_\_

WTE-010824

 1600 Ritchie Court  
Rochelle, IL 61068  
P 800.310.8823  
F 310.604.9785

westerntube.com  
Follow us on Twitter:  
@WesternTube

