# **SmartSet™ EMT**

Submittal Sheet

SmartSet EMT with built-in set screw coupling saves time and money on every job. The engineered steel set screw coupling comes built into one end of every piece of EMT and allows for up to 5x faster installation compared to standard set screw couplings. SmartSet EMT is available in trade sizes 1½-4 in 10' and 20' lengths.

### Listing

SmartSet EMT is listed to safety standards UL-797 and UL-514B for fittings, and it is manufactured in accordance with ANSI® C80.3.

#### Locations

SmartSet EMT is to be installed in accordance with the requirements of the National Electrical Code® Articles 358 (Electrical Metallic Tubing) and 358.42 (Couplings and Connectors). It is acceptable for use in all locations where standard EMT is allowed with associated fittings.

## SmartSet EMT Weights, Dimensions and Packaging (10' and 20' Lengths)

Trade Size	Metric Designator		side neter		ide neter*	Weight/ft.		Bundle ity—10'	Master Bundle Weight—10'	Master Quanti	Bundle ty — 20'	Master Bundle Weight — 20'
		in.	mm	in.	mm	lbs.	pieces	ft.	lbs.	pieces	ft.	lbs.
11/4	35	1.510	38.35	1.380	35.05	0.95	84	840	798	50	1000	950
1½	41	1.740	44.20	1.610	40.89	1.10	72	720	792	36	720	792
2	53	2.197	55.80	2.067	52.50	1.40	50	500	700	36	720	1008
21/2	63	2.875	73.03	2.731	69.37	2.05	35	350	718	20	400	820
3	78	3.500	88.90	3.356	85.24	2.50	30	300	750	20	400	1000
3 1/2	91	4.000	101.60	3.834	97.38	3.25	25	250	813	20	400	1300
4	103	4.500	114.30	4.334	110.08	3.70	25	250	925	12	240	888

<sup>\*</sup> For information only; not a UL-797 requirement.

SmartSet EMT with integral set screw coupling is available in 10' and 20' lengths through special order for standard EMT. Minimum order quantities apply.

## **Submittal Information**

PROJECT:	CONTRACTOR:	DATE:
ENGINEER:	SPECIFICATION REFERENCE:	SYSTEM TYPE:
LOCATIONS:	COMMENTS:	

WTE-010824



