



LIGHTWEIGHT & **CORROSION- RESISTANT**

RIGID ALUMINUM CONDUIT

Designed to provide decades of reliable service, rigid aluminum conduit is a lightweight, nonmagnetic wiring solution for dry, wet, exposed, concealed or hazardous locations.

Add your customized Call To Action here.
Add your customized Call To Action here.





Rigid Aluminum Conduit

Includes coupling on one end and color-coded thread protector on the other.

- Available in 10' and 15' lengths
- Easy to cut and bend
- Threaded on both ends
- Marine-grade alloy
- 6063 aluminum
- T-1 temper
- Complies with ANSI® C80.5
- Conforms to UL-6A

Rigid Aluminum Conduit Weights and Specifications (10' Lengths)

Trade Size	Metric Designator	Nominal OD	Nominal ID	Nominal Wall Thickness	Nominal Wt. per Foot with Coupling	Feet in Sub-Bundle	Qty. in Master Bundle	Feet in Master Bundle	Nom. Wt. per Master Bundle	End Cap Color
	mm	in.	in.	in.	lbs.	ft.	qty.	ft.	lbs.	
½	16	0.840	0.632	0.104	0.281	100	-	2500	703	● Black
¾	21	1.050	0.836	0.107	0.374	100	-	2500	935	● Red
1	27	1.315	1.063	0.126	0.545	100	-	2000	1090	● Blue
1¼	35	1.660	1.394	0.133	0.716	-	100	1000	716	● Red
1½	41	1.900	1.624	0.138	0.887	-	100	1000	887	● Black
2	53	2.375	2.083	0.146	1.185	-	45	450	533	● Blue
2½	63	2.875	2.489	0.193	1.875	-	30	300	563	● Black
3	78	3.500	3.090	0.205	2.463	-	20	200	493	● Blue
3½	91	4.000	3.570	0.215	2.956	-	20	200	591	● Black
4	103	4.500	4.050	0.225	3.502	-	20	200	700	● Blue
5	129	5.563	5.073	0.245	4.789	-	8	80	383	● Blue
6	155	6.625	6.093	0.266	6.304	-	6	60	378	● Blue

Master bundle quantities conform to NEMA Standard RN-2. All Western Tube conduit is UL® Listed.

Add your customized Call To Action here.
Add your customized Call To Action here.